

## Loudspeaker Management Processors

# TLM

## LMS-D26

2 Input, 6 Output Digital Loudspeaker Management System with BV-Net Card



- 2 input, 6 output digital loudspeaker management system processor with BV-Net card
- State-of-the-art DSP implementation for highest signal integrity
- Crossover filters up to 48 dB/oct with Butterworth, Bessel and Linkwitz-Riley responses
- High pass filter, 2 shelving filters, 6 parametric EQs and 400 ms of delay on each input
- 2 shelving filters, 6 parametric EQs, 80 ms of delay and limiter on each output
- Comprehensive channel grouping and ganging options
- TURBODRIVE remote control software available for download at [turbosound.com](http://turbosound.com)
- Presets for TURBOSOUND passive and bi-amped speakers available for download
- Rugged 1U rackmount chassis for durability in portable applications
- Auto-ranging universal switch-mode power supply
- 3-Year Warranty Program\*
- Designed and engineered in England

The **TURBOSOUND** LMS-D26 digital loudspeaker management system is a compact and powerful DSP based 2-in 6-out audio processing unit, ideally suited to live sound and fixed installation applications, and designed for use with **TURBOSOUND** loudspeakers and associated bass enclosures and subwoofers. It provides tailored equalisation and crossover functions specific to **TURBOSOUND** loudspeaker systems in a compact 1U high, 19" wide rack unit.



To achieve this, the LMS-D26 provides two inputs and six outputs, configured by factory presets, in addition to a total of 40 user-defined presets to enable use with a variety of loudspeakers. High performance limiters, delays (up to 400 ms input, 80 ms output), equalisation, gain, polarity, and crossover filter controls are accessible to the user in order to match specific operating environments. It provides exceptional audio quality through the use of carefully optimised processing and high performance converters for better than 111 dB of dynamic range, 96 kHz sampling rate and minimal filtering. It employs audio-grade capacitors in the analogue signal path for true audiophile performance and superior accuracy. The LMS-D26 features LF shelving filters to allow adjustment of the response in order to match variations of the acoustic conditions such as half space environments like floor monitor applications, or for close coupling of loudspeaker arrays. Input delays of up to 400 ms, and output delays of up to 80 ms can be set up on each output (mono) or pair of outputs (stereo) with fine resolution of 21  $\mu$ s steps to ensure perfect driver alignment.

Loudspeaker Management Processors

# TLM LMS-D26

2 Input, 6 Output Digital Loudspeaker  
Management System with BV-Net Card

The LMS-D26 is designed for quick setup and adjustment via an easy-to-use menu structure accessed by front panel buttons and rotary encoders. A high resolution back-lit LCD display provides the user interface to the menu options and parameters being adjusted. The LMS-D26 is equipped with a switching power supply that automatically adjusts to mains input voltages from 85 Volts to 240 Volts, allowing it be used anywhere in the world without inconvenient mains transformer adjustment.



## You Are Covered

We always strive to provide the best possible Customer Experience. Our products are made in our own **MUSIC Group** factory using state-of-the-art automation, enhanced production workflows and quality assurance labs with the most sophisticated test equipment available in the world. As a result, we have one of the lowest product failure rates in the industry, and we confidently back it up with a generous **3-Year Warranty** program.

## Loudspeaker Management Processors

# TLM LMS-D26

2 Input, 6 Output Digital Loudspeaker  
Management System with BV-Net Card

## Technical Specifications

### System

<b>Dimensions</b>	44 x 482 x 254 mm (1.75 x 19 x 10") Excluding Connectors
<b>Net Weight</b>	2.7 kg (5.9 lbs)
<b>Frequency Response</b>	10 Hz - 40 kHz $\pm$ 1 dB (Filters Disabled), 10 Hz - 20 kHz $\pm$ 0.25 dB (Filters Disabled)
<b>Connectors</b>	Input: 3-pin Female XLR, Output: 3-pin Male XLR
<b>Power Requirements</b>	Universal Switch Mode PSU, 85 V ~ 240 V AC, 50 ~ 60 Hz

Loudspeaker Management Processors

# TLM LMS-D26

2 Input, 6 Output Digital Loudspeaker Management System with BV-Net Card



Loudspeaker Management Processors

# TLM LMS-D26

2 Input, 6 Output Digital Loudspeaker Management System with BV-Net Card



For service, support or more information contact the TURBOSOUND location nearest you:

**Europe**  
**MUSIC Group Services UK**  
Tel: +44 156 273 2290  
Email: CARE@music-group.com

**USA/Canada**  
**MUSIC Group Services NV Inc.**  
Tel: +1 702 800 8290  
Email: CARE@music-group.com

**Japan**  
**MUSIC Group Services JP K.K.**  
Tel: +81 3 6231 0454  
Email: CARE@music-group.com

MUSIC Group accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. MIDAS, KLARK TEKNIK, LAB GRUPPEN, LAKE, TANNØY, TURBOSOUND, TC ELECTRONIC, TC HELICON, BEHRINGER, BUGERA and DDA are trademarks or registered trademarks of MUSIC Group IP Ltd.  
© MUSIC Group IP Ltd. 2016 All rights reserved.

