

HEAVY METAL HM300

Heavy Metal Distortion Effects Pedal

Thank you for showing your confidence in us by purchasing the Behringer HEAVY METAL HM300. This high-quality effects pedal enables you to produce super thick, tube-like distortion plus endless sustain. Thanks to its high-performance features you can achieve the typical hard rock or heavy metal distortion sounds.

1. Controls



- 1 The **LEVEL** control adjusts the output level.
- 2 The **LOW** control allows you to boost/cut the low-frequency range.
- 3 The **MID** control allows you to boost/cut the mid-frequency range.
- 4 The **DIST** control adjusts the amount of distortion effect and the length of the resulting sustain time. High distortion settings will cause longer sustain times.
- 5 The **ON/BATT** LED illuminates when the effect is activated. It also serves as a battery level indicator.
- 6 Use the footswitch to activate/deactivate the effect.
- 7 Use this 1/4" TS **IN** connector to plug in the instrument cable.
- 8 The 1/4" TS **OUT** connector sends the signal to your amp.

Use the **DC IN** connection to plug in a 9 V power supply (not included).

The **BATTERY COMPARTMENT** is located underneath the pedal cover. To install or replace the 9 V battery (not included), press the hinges with a ballpoint pen and remove the pedal cover. Be careful not to scratch the unit.

♦ **The HM300 has no on/off switch. As soon as you insert the plug into the in connector, the HM300 is on. When not in use, remove the plug from the in connector. This extends the life of the battery.**

The **SERIAL NUMBER** is located at the underside.

2. Safety Instructions

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

3. Limited Warranty

For the applicable warranty terms and conditions and additional information regarding Music Tribe's Limited Warranty, please see complete details online at musictribe.com/warranty.

4. Specifications

In

Connector	¼" TS
Impedance	500 kΩ

Out

Connector	¼" TS
Impedance	1 kΩ
Power Supply	9 V $\overline{-}$, 100 mA regulated
Behringer PSU-SB	100 - 240 V $\overline{-}$, 50 - 60 Hz
Power connector	2 mm DC jack, negative center
Battery	9 V type 6LR61
Power consumption	30 mA
Dimensions (H x W x D)	54 x 70 x 123 mm (2.1 x 2.8 x 4.8")
Weight	0.33 kg (0.73 lbs)

Behringer is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

Music Tribe accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. Midas, Klark Teknik, Lab Gruppen, Lake, Tannoy, Turbosound, TC Electronic, TC Helicon, Behringer, Bugera, Oberheim, Auratone and Coolaudio are trademarks or registered trademarks of Music Tribe Global Brands Ltd. © Music Tribe Global Brands Ltd. 2021 All rights reserved.

