

## Portable Speakers

# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications

- 2 way full range loudspeaker for portable PA and installation applications
- 800 Watts continuous, 3,200 Watts peak power
- Ideal for FOH, side and drum fill applications
- Carbon fibre loaded 12" low frequency driver with inside/outside wound coil
- Titanium dome 1.4" neodymium motor compression driver
- Switchable passive/bi-amp operation for flexibility of use
- Low distortion waveguide provides 90° H x 50° V dispersion
- 15 mm (5/8") birch plywood enclosure with hard wearing semi matt black paint finish
- Rugged powder coated perforated steel mesh grille
- Dual angle pole mount for accurate audience coverage
- Durable handles for easy lifting and carrying
- Multiple internal rigging points for installation applications
- Neutrik speakON\* NL4 connectors for reliable long life operation
- 3-Year Warranty Program\*
- Designed and engineered in England



The 2 way full range TMS122M is a switchable passive/bi-amp 12" 3,200 Watt loudspeaker system that is ideally suited for a wide range of portable speech and music sound reinforcement applications. The TMS122M is designed to work in conjunction with **TURBOSOUND** loudspeaker management systems, providing optimal performance for FOH, side fill and floor monitor applications, as well as offering considerable flexibility to readily adapt to varying venue requirements.



The TMS122M loudspeaker features a carbon fibre loaded 12" low frequency driver with inside/outside wound coil with low mass voice coil for improved transient response, and a titanium dome 1.4" neodymium motor compression driver mounted on a 90° horizontal by 50° vertical low distortion waveguide. All drivers are matched with an internal passive crossover network in a reflex-loaded enclosure, and bi-amp mode can be enabled by means of a rear panel switch.

Finished in a highly durable semi matt black paint, the cabinet is constructed from 15 mm (5/8") birch plywood, and includes a rugged powder coated perforated steel mesh grille backed with reticulated foam. The TMS122M includes internal M10 threaded rigging points for permanent installation, a dual-angle pole mount socket for high or low height use with 35 mm poles/speaker stands to optimise audience coverage, and durable handles for easy transport. The dual angle wedge shape design also enables the TMS122M to be utilised in low profile stage monitor applications where improved audience line of sight is of paramount importance. Two Neutrik speakON\* NL4 connectors are provided for input and link connections to additional enclosures.

\*All third-party trademarks are the property of their respective owners. Their use neither constitutes a claim of the trademark nor affiliation of the trademark owners with MUSIC Group. Product names are mentioned solely as a reference for compatibility, effects and/or components. Warranty details can be found at music-group.com.

Portable Speakers

# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications



## You Are Covered

We always strive to provide the best possible Customer Experience. Our products are made in our own **MUSIC Group** factory using state-of-the-art automation, enhanced production workflows and quality assurance labs with the most sophisticated test equipment available in the world.


As a result, we have one of the lowest product failure rates in the industry, and we confidently back it up with a generous **3-Year Warranty program**.

Portable Speakers


# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications

## Frequency Response Sensitivity 1 W / 1 m



## Impedance




Portable Speakers


# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications

## Horizontal Beamwidth



## Vertical Beamwidth








Portable Speakers

# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications

## Horizontal Polar Plots








Portable Speakers

# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications

## Vertical Polar Plots




Portable Speakers


# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications


## Dimensions




TOP




BOTTOM




LEFT SIDE



FRONT



RIGHT SIDE



BACK

## Portable Speakers

# MADRID

## TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications

### Technical Specifications

#### System

<b>Frequency Response</b>	65 Hz – 18 kHz $\pm$ 3 dB 50 Hz – 20 kHz -10 dB
<b>Nominal Dispersion</b>	90° H X 50° V @ -6 dB Points
<b>Directivity Factor (Q)</b>	10.4
<b>Directivity Index (DI)</b>	10.2
<b>Power Handling (IEC)</b>	
Passive	800 W continuous, 3,200 W peak
Bi-amp	LF: 800 W continuous, 3,200 W peak HF: 75 W continuous, 300 W peak
<b>Sensitivity</b>	96 dB (1 W @ 1 m)
<b>Maximum SPL</b>	
Passive	125 dB continuous, 131 dB peak
Bi-Amp	LF: 125 dB continuous, 131 dB peak HF: 128 dB continuous, 134 dB peak
<b>Impedance</b>	
Passive	8 $\Omega$
Bi-Amp	LF: 8 $\Omega$ HF: 6 $\Omega$
<b>Crossover Type</b>	Passive / Bi-amp, switchable
<b>Components</b>	1 x 12" (316 mm) LF driver 1 x 1.4" (36 mm) HF compression driver

#### Enclosure


<b>Connectors</b>	2 x Neutrik speakON* NL4
<b>Wiring</b>	
Passive	Pins 1+ / 1- input, pins 2+ / 2- link
Bi-Amp	Pins 1+ / 1- LF, pins 2+ / 2- HF
<b>Dimensions HWD</b>	566 x 349 x 283 mm (22.3 x 13.7 x 11.1")
<b>Net Weight</b>	18.2 kg (40.0 lbs)
<b>Construction</b>	15 mm (5/8") birch plywood
<b>Finish</b>	Semi matt black paint
<b>Grille</b>	Powder-coated perforated steel
<b>Flying Hardware</b>	M10 x 2



Portable Speakers

# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications



Portable Speakers

# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications



Portable Speakers

# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications



Portable Speakers

# MADRID TMS122M

2 Way 12" Full Range Loudspeaker for  
Portable PA and Installation Applications



For service, support or more information contact the TURBOSOUND location nearest you:

**Europe**  
**MUSIC Group Services UK**  
Tel: +44 156 273 2290  
Email: CARE@music-group.com

**USA/Canada**  
**MUSIC Group Services NV Inc.**  
Tel: +1 702 800 8290  
Email: CARE@music-group.com

**Japan**  
**MUSIC Group Services JP K.K.**  
Tel: +81 3 6231 0454  
Email: CARE@music-group.com

MUSIC Group accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. MIDAS, KLARK TEKNIK, LAB GRUPPEN, LAKE, TANNÖY, TURBOSOUND, TC ELECTRONIC, TC HELICON, BEHRINGER, BUGERA and DDA are trademarks or registered trademarks of MUSIC Group IP Ltd.  
© MUSIC Group IP Ltd. 2016 All rights reserved.

