


SUPER FUZZ SF300

3-Mode Fuzz Distortion Effects Pedal

Thank you for showing your confidence in us by purchasing the BEHRINGER SUPER FUZZ SF300. This effects pedal is ideally suited for electric guitars and recreates the whole variety of famous fuzz tones of the '60s and '70s.

1. Controls



- 1 The **LEVEL** control adjusts the output level.
- 2 The **TREBLE** control allows you to boost/cut the high-frequency range.
- 3 The **BASS** control allows you to boost/cut the low-frequency range.
- 4 The **GAIN** control adjusts the gain for more distorted sounds.
- 5 The **MODE** switch lets you choose between 3 effect modes.
FUZZ 1: Basic fuzz sound with emphasis on the midrange.
FUZZ 2: Full-bodied fuzz sound with scooped mids and sharp harmonics.
BOOST: The Level control is inactive and the Gain control adjusts the boost.
- 6 The **ON/BATT** LED illuminates when the effect is activated. It also serves as a battery level indicator.
- 7 Use the footswitch to activate/deactivate the effect.
- 8 Use this 1/4" TS **IN** connector to plug in the instrument cable.
- 9 The 1/4" TS **OUT** connector sends the signal to your amp.

Use the **DC IN** connection to plug in a 9 V power supply (not included).

The **BATTERY COMPARTMENT** is located underneath the pedal cover. To install or replace the 9 V battery (not included), press the hinges with a ballpoint pen and remove the pedal cover. Be careful not to scratch the unit.

- ◆ **The SF300 has no on/off switch. As soon as you insert the plug into the in connector, the SF300 is on. When not in use, remove the plug from the in connector. This extends the life of the battery.**

The **SERIAL NUMBER** is located at the underside.

2. Safety Instructions

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

3. Limited Warranty

For the applicable warranty terms and conditions and additional information regarding MUSIC Tribe's Limited Warranty, please see complete details online at musictri.be/warranty.

4. Specifications

In	
Connector	¼" TS
Impedance	500 kΩ

Out	
Connector	¼" TS
Impedance	1 kΩ

Power Supply	
	9 V $\overline{=}$, 100 mA regulated
BEHRINGER PSU-SB	
USA/Canada	120 V \sim , 60 Hz
Europe/U.K./Australia	230 V \sim , 50 Hz
China	220 V \sim , 50 Hz
Korea	220 V \sim , 60 Hz
Japan	100 V \sim , 50/60 Hz

Power connector	2 mm DC jack, negative center
Battery	9 V type 6LR61
Power consumption	30 mA

Physical/Weight	
Dimensions (H x W x D)	approx. 2 ½ x 2 ¾ x 4 ½"
	approx. 54 x 70 x 123 mm
Weight	approx. 0.73 lbs / 0.33 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

MUSIC Tribe accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. MIDAS, KLARK TEKNIK, LAB GRUPPEN, LAKE, TANNOY, TURBOSOUND, TC ELECTRONIC, TC HELICON, BEHRINGER, BUGERA and COOLAUDIO are trademarks or registered trademarks of MUSIC Tribe Global Brands Ltd. © MUSIC Tribe Global Brands Ltd. 2018 All rights reserved.

